

TF4

EN_TF4_CTS_22-08_r8.0

The new TF4 is the smallest model of the Generac Mobile® range. This portable lighting tower is extremely practical and easy to use, ensuring a good level of illumination for small-sized working areas. The Hyper floodlights can be rotated and tilted in different positions to illuminate from 180° up to 360°. TF4 is ideal for applications in containers, mobile offices, temporary dormitories, power factories and also perfect for use by Civil Protection.



GENERAC® HYPER LED

High efficiency LED floodlights designed by Generac Mobile®. Any floodlight can be pointed in different directions.



Version with electric mast

MCP - MANUAL CONTROL PANEL

Manual control panel with electric circuit breakers, AC fuse protection, earth pin, darkness sensor and electric mast. Option: manual lifting system.

LINKABILITY

The operator can connect up to six* TF4 units in series to a single external power source, providing a wide illumination area with a reduced fuel consumption.

TF4

TECHNICAL DATA

Min. dimensions (mm)	Length x Width x Height	662 x 586 x 1505
Max. dimensions (mm)	Length x Width x Height	1615 x 1615 x 4200
Dry weight (kg)		104
Mast lifting system	M: Manual / E: Electric	E
Wind speed resistance (km/h)		80
Lamps power (W)		4 x 100
Lamps type		LED
Total lumen (Lm)		58000
Illuminated area (m ²)		850
CEE outlet socket	A/N/Hz	16/230/50 - 16/240/60
CEE inlet plug	A/N/Hz	16/230/50 - 16/240/60
Max. units in series*		6

* With 4mm cable section. Max. distance between units: 50m