


V20 PRO HYPER AGM

EN_V20-PRO-Hyper-AGM_CTS_22-08_r8.0

V20 PRO is not just a new lighting tower, but the real and only "ALL IN ONE" product! It embodies all the innovations and new technologies that Generac Mobile® has developed in over 20 years at the top of the industry as manufacturer. We have brought together all the Rental needs, in one single product. Special version with Hyper LED floodlights.



GENERAC® HYPER LED

LED floodlights placed on special brackets to point them in any direction.

ALL IN ONE

PRO is the only lighting tower technology to offer altogether:

- 1) the **future**, with 100% battery-powered supply;
- 2) the **present**, with the latest generation hybrid power supply;
- 3) the **tradition**, with low consumption diesel engine.

All in one model.

Engine note: both EU Stage V and unregulated version available.

V20 PRO Hyper AGM K2

TECHNICAL DATA					
Min. dimensions* (mm)	Length x Width x Height	2245 x 1431 x 2424			
Max. dimensions* (mm)	Length x Width x Height	3390 x 1714 x 8200			
Dry weight* (kg)		1146			
Battery type		AGM			
Engine model		Kubota Z482			
Avg. sound pressure	dB(A) @ 7m	0 - 58			
Dimmer switch	Light intensity	25%	50%	75%	100%
Max. lamps power (W)		4 x 60	4 x 120	4 x 180	4 x 240
Lamps type		Hyper LED	LED	LED	LED
Max. total lumen (Lm)		41040	76184	107668	139200
Max. illuminated area (m ²)		1500	2200	2700	3100
Battery recharging time (h)		6:11	5:18	5:09	4:29
Running time - Battery mode (h)		19:46	10:07	5:11	3:45
Running time - Generator mode (h)		165	151	134	125
Running time - Hybrid mode (h)		471	303	202	180
Mast lifting system	M: Manual / H: Hydraulic	H			
Mast rotation (°)		340			
Wind speed resistance (km/h)		110			
Alternator	kVA/V/Hz	5/230/50 - 5/240/60			
CEE inlet plug (external power)	A/V/Hz	16/230/50 - 16/240/60			
Multipin inlet plug (solar kit)	√: Yes / ●: No	√			
Tank capacity (liters)		100 (90 net)			
Liquid containment tank (110%)	√: Yes / ●: No	√			

*Values refer to version with adjustable road trailer